

# 16GB Computer memory DDR3 for Fujitsu Primergy TX300 S5 RDIMM

	<b>phs</b> memory <sup>®</sup>		
	42,27 EUR plus VAT 50,30 EUR incl. VAT		
	in magazzino https://www.phs-memory.it Version: 28.08.2025 02:34		
	Your benefits		
	verified quality memory		
	5 years warranty Warranty details see last page		
	✓ 100% compatible		
	✓ free support on our hotline		
	✓ fast delivery		

### PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



# Memory Specification

4	- 133.35mm		
DR3 RDIM   warranty void if removed   54.68mm		17.3mm 9.5mm	30mm

Memory size	16GB
Memory technology	DDR3
ECC support	ја
JEDEC Norm	PC3-10600R
DRAM Organization	1Gx4
Rank	2Rx4
Туре	RDIMM (ECC Registered)
Number of pins	240 Pin DIMM
Memory data transfer rate	1333MHz @ CL9
Speciality	-, DDP
Board dimensions	133,35 x 30 (LxB mm)
Operating temperature	0° C - 85° C
Storage temperature	-40° C - +95° C
RoHS compliant	Yes
SKU	SP154737
EAN	4055069035520
Operating temperature Storage temperature	0° C - 85° C -40° C - +95° C

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



### System Specifications

The memory is 100% compatible with this sytem:

System manufacturer	Fujitsu
Device type	Server
Device family	Primergy
Device series	TX300 Serie
Device name	Primergy TX300 S5
Maximum memory*	576GB / 384GB according to manufacturer
Number of memory sockets	18
Annotation	Don´t mix ECC UDIMM and RDIMM server memory in one system. Both technologies can be used and extended without any problems alone.

\* The specifications for the maximum memory upgrade may differ from those of the manufacturer Fujitsu. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

### Information on memory allocation

#### Computer memory Upgrade Primergy TX300 S5

The maximum configuration of the computer memory is possible with 12 x 32GB RDIMM memories to 384GB.

Your server has 9 memory slots per CPU that are organized in 3 slot groups of 3 slots each. Bei 2 CPUs ergeben sich dawith 18 memorysteckplätze for server Computer memory.

Es können pro Slotgruppe jeweils 2 memory slots with 32GB RDIMM bestückt werden.

To achieve good system performance, it is recommended to distribute the memory evenly among the memory slots and evenly among the CPUs.

With the assembly of 3 identical memories per 3 slot group and the assembly of all slot groups, the performance in peak loads is up to 3 times faster than with a single assembly of the 3 slot group.

The different groups of 3 slots do not have to have the same capacities.

If there is more than one CPU, the memory per CPU should be identically populated (mirrored to the other CPU). Es können nur die memorysteckplätze genutzt werden, bei denen die jeweilige CPU vorhanden ist.

### Information on memory installation

Turn off the system



- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
- Do not touch the gold pins of the memory module
- Only touch the sides of the memory module
- Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



### Further memory options for Fujitsu Primergy TX300 S5

Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
8GB	SP105934	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
16GB	SP154737	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	S26361-F3383-L 427
8GB	SP154736	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
32GB	SP154739	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
16GB	SP154738	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	S26361-F3383-L 427
32GB	SP154740	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	

#### PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.it/-W5Y



# Contact Information

PHS-electronic gmbh - www.phs-memory.it -Karl-Götz-Str. 5 97424 Schweinfurt Germania Phone: +49 9721 784678 E-Mail: info@phs-memory.it Web: www.phs-memory.it

All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.it