phs memory®

64GB Computer memory DDR4 for Supermicro SuperServer SYS-220BT-HNC9R RDIMM

phs memory®
214,87 EUR plus VAT 255,70 EUR incl. VAT in magazzino
https://www.phs-memory.it Version: 08.09.2025 03:34
verified quality memory
S years warranty Warranty details see last page
✓ 100% compatible
free support on our hotline
✓ fast delivery

PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



Memory Specification



Memory size	64GB
Memory technology	DDR4
ECC support	ja
JEDEC Norm	PC4-25600R
DRAM Organization	4Gx4
Rank	2Rx4
Туре	RDIMM (ECC Registered)
Number of pins	288 Pin DIMM
Memory data transfer rate	3200MHz @ CL22
Voltage	1,2 Volt
Speciality	-, DDP
Board dimensions	133,35 x 31,25 (LxB mm)
Operating temperature	0° C - 85° C
Storage temperature	-40° C - +95° C
RoHS compliant	Yes
SKU	SP380353
EAN	4064578434533

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



System Specifications

The memory is 100% compatible with this sytem:

System manufacturer	Supermicro
Device type	Server
Device family	SuperServer
Device series	SYS-220 Serie
Device name	SuperServer SYS-220BT-HNC9R
Maximum memory*	4TB
Number of memory sockets	16

* The specifications for the maximum memory upgrade may differ from those of the manufacturer Supermicro. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Information on memory allocation

Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- When using a multiprocessor system, the memory slots should always be configured identically for each CPU.
- Memory slots without a processor may not be used.
- If memory modules are provided with higher speeds than specified by the system, the memory speed is automatically adjusted to the system specifications.

Maximum memory speed of possible CPUs

Xeon CPUs of the 3nd generation are offered in Bronze, Silver, Gold or Platinum. The different processor series also support different maximum memory speeds:

Xeon	CPU-series	max. Speed MHz	max. memory capacity je CPU	CPU xxxxH	CPU xxxxHL
Silver	4300	2666	6 TB		
Gold	5300	2933	6 TB	1,2 TB	4,5 TB
Gold	6300	3200	6 TB	1,2 TB	4,5 TB
Platinum	8300	3200	6 TB	1,2 TB	4,5 TB

Information on memory installation



- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
 - Do not touch the gold pins of the memory module
 - Only touch the sides of the memory module
 - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



Further memory options for Supermicro SuperServer SYS-220BT-HNC9R

Registered) ER32 32GB SP380352 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® MEM-DR432LC- ER32	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered)Registered)ER3232GBSP380352DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory® RER32MEM-DR432LC- ER3264GBSP380353DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory® RER32MEM-DR464MC ER3264GBSP380349DDR4LRDIMM (ECC 	8GB	SP473368	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered)ER3264GBSP380353DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory®MEM-DR464MC ER3264GBSP380349DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®MEM-DR464MC ER32128GBSP470326DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®C128GBSP380350DDR4RDIMM (ECC Registered) 3DS288 Pin DIMMPHS-memory®C256GBSP470328DDR4RDIMM (ECC Registered) 3DS288 Pin DIMMPHS-memory®	16GB	SP380351	DDR4	`	288 Pin DIMM	PHS-memory®	MEM-DR416LD- ER32
Registered)ER3264GBSP380349DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP470326DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP380350DDR4RDIMM (ECC Registered) 3DS288 Pin DIMMPHS-memory®256GBSP470328DDR4RDIMM (ECC 	32GB	SP380352	DDR4	`	288 Pin DIMM	PHS-memory®	MEM-DR432LC- ER32
LR DIMM)LR DIMM)LR DIMMPHS-memory®128GBSP470326DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP380350DDR4RDIMM (ECC Registered) 3DS288 Pin DIMMPHS-memory®256GBSP470328DDR4RDIMM (ECC Registered) 3DS288 Pin DIMMPHS-memory®	64GB	SP380353	DDR4	`	288 Pin DIMM	PHS-memory®	MEM-DR464MC- ER32
LR DIMM) LR DIMM) 128GB SP380350 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP470328 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory®	64GB	SP380349	DDR4	``	288 Pin DIMM	PHS-memory®	
Registered) 3DS 256GB SP470328 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP470326	DDR4	•	288 Pin DIMM	PHS-memory®	
	128GB	SP380350	DDR4	•	288 Pin DIMM	PHS-memory®	
	256GB	SP470328	DDR4	•	288 Pin DIMM	PHS-memory®	
256GB SP470327 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM) 3DS	256GB	SP470327	DDR4	· ·	288 Pin DIMM	PHS-memory®	

PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.it/-W5Y



Contact Information

PHS-electronic gmbh - www.phs-memory.it -Karl-Götz-Str. 5 97424 Schweinfurt Germania Phone: +49 9721 784678 E-Mail: info@phs-memory.it Web: www.phs-memory.it



All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.it