

128GB Computer memory DDR4 for Gigabyte R282-Z92 (rev. 100) LRDIMM





Your benefits ✓ verified quality memory ✓ 5 years warranty Warranty details see last page ✓ 100% compatible ✓ free support on our hotline ✓ fast delivery

PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



Memory Specification



Memory size	128GB
Memory technology	DDR4
ECC support	yes
JEDEC Norm	PC4-25600-L
DRAM Organization	8Gx4
Rank	4Rx4 (4DRx4 DDP)
Туре	LRDIMM (ECC LR DIMM)
Number of pins	288 Pin DIMM
Memory data transfer rate	3200MHz @ CL22
Voltage	1,2 Volt
Speciality	DDP
Board dimensions	133,35 x 31,25 (LxB mm)
Operating temperature	0° C - 85° C
Storage temperature	-40° C - +95° C
RoHS compliant	yes
SKU	SP472433
EAN	4067488359422

overRAMing - maximize your RAM



Most systems - including the Gigabyte R282-Z92 (rev. 100) - can be upgraded with more memory than originally specified by the device manufacturer.

Therefore, our memory specialists continuously analyze new memory solutions in selected systems. Due to improved manufacturing technologies, new memories with higher performance and capacity will be tested for stability and functionality.

Then the new memory solutions are released for the respective systems. Use the benefits of larger computer memory capacity with the PHSmemory® overRAMing memory solutions.

https://www.phs-memory.it/-BOR

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



System Specifications

The memory is 100% compatible with this sytem:

System manufacturer	Gigabyte
Device type	Server
Device family	Rack Server
Device series	R282 Serie
Device name	R282-Z92 (rev. 100)
Maximum memory*	8TB / 2TB according to manufacturer
Number of memory sockets	32

^{*} The specifications for the maximum memory upgrade may differ from those of the manufacturer Gigabyte. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Memory modules with our overRAMing-symbol are approved by us for maximum memory expansion.

Information on memory allocation

Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.

Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
 - Do not touch the gold pins of the memory module
 - Only touch the sides of the memory module
 - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



Further memory options for Gigabyte R282-Z92 (rev. 100)

8GB SP366872 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 16GB SP366869 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 32GB SP366870 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP366871 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP366868 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP472433 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469720 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 128GB SP469717 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory®	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered) 32GB SP366870 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP366871 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP366868 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP472433 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469720 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469717 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory®	8GB	SP366872	DDR4	,	288 Pin DIMM	PHS-memory®	
Registered) 64GB SP366871 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP366868 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP472433 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469720 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469717 DDR4 LRDIMM (ECC LR DIMM) (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory®	16GB	SP366869	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 64GB SP366868 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP472433 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469720 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469717 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory®	32GB	SP366870	DDR4	,	288 Pin DIMM	PHS-memory®	
LR DIMM) 128GB SP472433 DDR4 LRDIMM (ECC LR DIMM) 128GB SP469720 DDR4 RDIMM (ECC Registered) 3DS 128GB SP469717 DDR4 LRDIMM (ECC LR DIMM) PHS-memory® LR DIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® LR DIMM (ECC LR DIMM) 3DS	64GB	SP366871	DDR4	,	288 Pin DIMM	PHS-memory®	
LR DIMM) 128GB SP469720 DDR4 RDIMM (ECC Registered) 3DS 128GB SP469717 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM) 3DS	64GB	SP366868	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 3DS 128GB SP469717 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM) 3DS	128GB	SP472433	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 3DS	128GB	SP469720	DDR4	•	288 Pin DIMM	PHS-memory®	
25,650 604,6733 0004 0004 0004 000 000 0004	128GB	SP469717	DDR4	•	288 Pin DIMM	PHS-memory®	
256GB SP469722 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® Registered) 3DS	256GB	SP469722	DDR4	RDIMM (ECC Registered) 3DS	288 Pin DIMM	PHS-memory®	
256GB SP469719 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM) 3DS	256GB	SP469719	DDR4	•	288 Pin DIMM	PHS-memory®	

PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.it/-W5Y



Contact Information

PHS-electronic gmbh - www.phs-memory.it - Karl-Götz-Str. 5 97424 Schweinfurt Germania

Phone: +49 9721 784678 E-Mail: info@phs-memory.it Web: www.phs-memory.it

Product Datasheet | SP472433 128GB Computer memory for R282-Z92 (rev. 100)



All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.it