

## 64GB Computer memory DDR4 for Fujitsu Primergy RX2510 M2 (D3279-H100) RDIMM 3DS



phs memory®

**189,66 EUR**

plus VAT

**225,70 EUR**

incl. VAT

in magazzino

<https://www.phs-memory.it>

Version: 02.09.2025 19:26

### Your benefits

- ✓ verified quality memory
- ✓ 5 years warranty  
Warranty details see last page
- ✓ 100% compatible
- ✓ free support on our hotline
- ✓ fast delivery

## PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device - depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel

## Memory Specification



<b>Memory size</b>	64GB
<b>Memory technology</b>	DDR4
<b>ECC support</b>	ja
<b>JEDEC Norm</b>	PC4-21300R
<b>DRAM Organization</b>	3DS 2H 4Gx4
<b>Rank</b>	4Rx4 (2S2Rx4)
<b>Type</b>	RDIMM (ECC Registered) 3DS
<b>Number of pins</b>	288 Pin DIMM
<b>Memory data transfer rate</b>	2666MHz @ CL19
<b>Voltage</b>	1,2 Volt
<b>Speciality</b>	3DS
<b>Board dimensions</b>	133,35 x 31,25 (LxB mm)
<b>Operating temperature</b>	0° C - 85° C
<b>Storage temperature</b>	-40° C - +95° C
<b>RoHS compliant</b>	Yes
<b>SKU</b>	SP469250
<b>EAN</b>	4067488327759

Note: The module specified in this datasheet is one of several possible configurations available under this part number. Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.

## System Specifications

The memory is 100% compatible with this system:

<b>System manufacturer</b>	Fujitsu
<b>Device type</b>	Server
<b>Device family</b>	Primergy
<b>Device series</b>	RX2500 Serie
<b>Device name</b>	Primergy RX2510 M2 (D3279-H100)
<b>Maximum memory*</b>	1,5TB / 768GB according to manufacturer
<b>Number of memory sockets</b>	12

\* The specifications for the maximum memory upgrade may differ from those of the manufacturer Fujitsu. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

## Information on memory allocation

### Information on memory configuration

The following technical specifications should be considered in advance:

- Memory slots without a processor may not be used.
- A higher memory clock of the memory module automatically adapts to the memory clock specified by the system. This can be the case especially with larger capacities.

### Computer memory for Systeme with XEON E5-2600 v4 CPU:

CPU im System	RDIMM
Xeon E5-2600 v4 (1 Processor configuration)	until zu 12 x 16GB RDIMM until zu 12 x 32GB RDIMM until zu 12 x 64GB RDIMM until zu 12 x 128GB RDIMM
Xeon E5-2600 v4 (2 Processor configuration)	until zu 24 x 16GB RDIMM until zu 24 x 32GB RDIMM until zu 24 x 64GB RDIMM until zu 24 x 128GB RDIMM

Xeon E5-2600 v4 (4 Processor configuration)

until zu 48 x 16GB RDIMM

until zu 48 x 32GB RDIMM

until zu 48 x 64GB RDIMM

until zu 48 x 128GB RDIMM

## Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
  - Do not touch the gold pins of the memory module
  - Only touch the sides of the memory module
  - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.

## Further memory options for Fujitsu Primergy RX2510 M2 (D3279-H100)

Size	SKU	Technology	Type	Number of pins	Brand	Reference no.
8GB	SP158032	DDR4	RDIMM (ECC Registered)	288 Pin DIMM	PHS-memory®	S26361-F3934-L511
16GB	SP158029	DDR4	RDIMM (ECC Registered)	288 Pin DIMM	PHS-memory®	S26361-F3934-L512
32GB	SP341751	DDR4	RDIMM (ECC Registered)	288 Pin DIMM	PHS-memory®	S26361-F3934-L515
64GB	SP464019	DDR4	RDIMM (ECC Registered)	288 Pin DIMM	PHS-memory®	
64GB	SP469250	DDR4	RDIMM (ECC Registered) 3DS	288 Pin DIMM	PHS-memory®	S26361-F3934-L517
128GB	SP469251	DDR4	RDIMM (ECC Registered) 3DS	288 Pin DIMM	PHS-memory®	

## PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit <https://www.phs-memory.it/-W5Y>



## Contact Information

PHS-electronic gmbh  
- [www.phs-memory.it](http://www.phs-memory.it) -  
Karl-Götz-Str. 5  
97424 Schweinfurt  
Germania

Phone: +49 9721 784678  
E-Mail: [info@phs-memory.it](mailto:info@phs-memory.it)  
Web: [www.phs-memory.it](http://www.phs-memory.it)

All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at <https://www.phs-memory.it>