

## 32GB Computer memory DDR3 for Supermicro X9DR7-TF+ LRDIMM






# Your benefits ✓ verified quality memory ✓ 5 years warranty Warranty details see last page ✓ 100% compatible ✓ free support on our hotline ✓ fast delivery

#### PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



#### Memory Specification



Memory technologyDDR3ECC supportjaJEDEC NormPC3L-12800LDRAM Organization2Gx4Rank4Rx4 (4DRx4 DDP)TypeLRDIMM (ECC LR DIMM)Number of pins240 Pin DIMMMemory data transfer rate1600MHz @ CL11Voltage1,35 VoltSpecialityDDPBoard dimensions133,35 x 30 (LxB mm)Operating temperature0° C - 85° C	Memory size	32GB		
JEDEC Norm  PC3L-12800L  DRAM Organization  2Gx4  Rank  4Rx4 (4DRx4 DDP)  Type  LRDIMM (ECC LR DIMM)  Number of pins  240 Pin DIMM  Memory data transfer rate  1600MHz @ CL11  Voltage  1,35 Volt  Speciality  DDP  Board dimensions  133,35 x 30 (LxB mm)	Memory technology	DDR3		
DRAM Organization2Gx4Rank4Rx4 (4DRx4 DDP)TypeLRDIMM (ECC LR DIMM)Number of pins240 Pin DIMMMemory data transfer rate1600MHz @ CL11Voltage1,35 VoltSpecialityDDPBoard dimensions133,35 x 30 (LxB mm)	ECC support	ja		
Rank 4Rx4 (4DRx4 DDP)  Type LRDIMM (ECC LR DIMM)  Number of pins 240 Pin DIMM  Memory data transfer rate 1600MHz @ CL11  Voltage 1,35 Volt  Speciality DDP  Board dimensions 133,35 x 30 (LxB mm)	JEDEC Norm	PC3L-12800L		
Type  LRDIMM (ECC LR DIMM)  Number of pins  240 Pin DIMM  Memory data transfer rate  1600MHz @ CL11  Voltage  1,35 Volt  Speciality  DDP  Board dimensions  133,35 x 30 (LxB mm)	DRAM Organization	2Gx4		
Number of pins240 Pin DIMMMemory data transfer rate1600MHz @ CL11Voltage1,35 VoltSpecialityDDPBoard dimensions133,35 x 30 (LxB mm)	Rank	4Rx4 (4DRx4 DDP)		
Memory data transfer rate1600MHz @ CL11Voltage1,35 VoltSpecialityDDPBoard dimensions133,35 x 30 (LxB mm)	Туре	LRDIMM (ECC LR DIMM)		
Voltage1,35 VoltSpecialityDDPBoard dimensions133,35 x 30 (LxB mm)	Number of pins	240 Pin DIMM		
Speciality DDP  Board dimensions 133,35 x 30 (LxB mm)	Memory data transfer rate	1600MHz @ CL11		
Board dimensions 133,35 x 30 (LxB mm)	Voltage	1,35 Volt		
,	Speciality	DDP		
Operating temperature $0^{\circ} \text{C-} 85^{\circ} \text{C}$	Board dimensions	133,35 x 30 (LxB mm)		
	Operating temperature	0° C - 85° C		
Storage temperature -40° C - +95° C	Storage temperature	-40° C - +95° C		
RoHS compliant Yes	RoHS compliant	Yes		
<b>SKU</b> SP261317	SKU	SP261317		
<b>EAN</b> 4063369297678	EAN	4063369297678		

### overRAMing - maximize your RAM



Most systems - including the Supermicro X9DR7-TF+ - can be upgraded with more memory than originally specified by the device manufacturer.

Therefore, our memory specialists continuously analyze new memory solutions in selected systems. Due to improved manufacturing technologies, new memories with higher performance and capacity will be tested for stability and functionality.

Then the new memory solutions are released for the respective systems. Use the benefits of larger computer memory capacity with the PHS-memory® overRAMing memory solutions.

https://www.phs-memory.it/-BOR

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



#### System Specifications

The memory is 100% compatible with this sytem:

Supermicro		
Server-Mainboard		
Mainboard X		
X9D Serie		
X9DR7-TF+		
768GB ECC / 128GB according to manufacturer		
24		
ECC DIMM, Registered DIMM and Load Reduced LRDIMM memory modules must not be mixed. Per processor, 12 memories can be installed.		

<sup>\*</sup>The specifications for the maximum memory upgrade may differ from those of the manufacturer Supermicro. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Memory modules with our overRAMing-symbol are approved by us for maximum memory expansion.

#### Information on memory allocation

#### Which memory configuration is possible?

Our memory team will be happy to help you choose the right memory and configure your server.

Technologie	RAM in maximaler capacity		
UDIMM ECC	128GB RAM 2 x (8 x 8GB ECC UDIMM)		
RDIMM 2Rank	384GB RAM 2 x (12 x 16GB RDIMM)		
RDIMM 4Rank	512GB RAM 2 x (8 x 32GB RDIMM)		
LRDIMM	1,5TB RAM 2 x (12 x 64GB LRDIMM)		

ECC DIMM, Registered DIMM and Load Reduced LRDIMM memory modules must not be mixed. Bei einer Aufrüstung sollten Sie deshalb wissen, welche memory bereits vorhanden sind, or komplett auf RDIMMcomputer memory upgrade.

#### Principles of memory assembly

- Pro CPU sind 4 memorykanäle vorhanden with jeweils 2 memoryslots
- Bei Einsatz of ECC UDIMM or 4Rank (4Rx..) RDIMM memoryn können nur jeweils 2 of 3 memoryslots pro memorykanal belegt werden
- ECC DIMM, Registered DIMM and Load Reduced LRDIMM memory modules must not be mixed
- memorysteckplätze for die kein Prozessor vorhanden ist dürfen nicht bestückt werden

#### Memory configuration for good system performance

#### Product Datasheet | SP261317 32GB Computer memory for X9DR7-TF+



- Verteilen Sie die memory gleichmäßig auf die memorysteckplätze and gleichmäßig auf die CPUs
- Wenn mehr als eine CPU vorhanden sind, sollten die memory pro CPU identisch (gespiegelt zur anderen CPU) bestückt werden.

#### Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
  - Do not touch the gold pins of the memory module
  - Only touch the sides of the memory module
  - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



#### Further memory options for Supermicro X9DR7-TF+

Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
4GB	SP261315	DDR3	UDIMM ECC (ECC unbuffered)	240 Pin DIMM	PHS-memory®	
8GB	SP261321	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
8GB	SP261316	DDR3	UDIMM ECC (ECC unbuffered)	240 Pin DIMM	PHS-memory®	
16GB	SP261318	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
32GB	SP261319	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
32GB	SP261317	DDR3	LRDIMM (ECC LR DIMM)	240 Pin DIMM	PHS-memory®	

#### PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.





#### Contact Information

PHS-electronic gmbh - www.phs-memory.it - Karl-Götz-Str. 5 97424 Schweinfurt Germania

Phone: +49 9721 784678 E-Mail: info@phs-memory.it Web: www.phs-memory.it

All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.it