

## 32GB Computer memory DDR3 for Supermicro X8DTU-6TF+ RDIMM





# Your benefits ✓ verified quality memory ✓ 5 years warranty Warranty details see last page ✓ 100% compatible ✓ free support on our hotline ✓ fast delivery

#### PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



#### Memory Specification



| Memory technologyDDR3ECC supportjaJEDEC NormPC3-10600RDRAM Organization2Gx4Rank4Rx4 (4DRx4 DDP)TypeRDIMM (ECC Registered)Number of pins240 Pin DIMMMemory data transfer rate1333MHz @ CL9SpecialityDDPBoard dimensions133,35 x 30 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantYes         | Memory size               | 32GB                   |  |  |
|--|---------------------------|------------------------|--|--|
| JEDEC Norm  PC3-10600R  DRAM Organization  2Gx4  Rank  4Rx4 (4DRx4 DDP)  Type  RDIMM (ECC Registered)  Number of pins  240 Pin DIMM  Memory data transfer rate  1333MHz @ CL9  Speciality  DDP  Board dimensions  133,35 x 30 (LxB mm)  Operating temperature  0° C - 85° C  Storage temperature  -40° C - +95° C  RoHS compliant  Yes | Memory technology         | DDR3                   |  |  |
| DRAM Organization2Gx4Rank4Rx4 (4DRx4 DDP)TypeRDIMM (ECC Registered)Number of pins240 Pin DIMMMemory data transfer rate1333MHz @ CL9SpecialityDDPBoard dimensions133,35 x 30 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantYes   | ECC support               | ja                     |  |  |
| Rank4Rx4 (4DRx4 DDP)TypeRDIMM (ECC Registered)Number of pins240 Pin DIMMMemory data transfer rate1333MHz @ CL9SpecialityDDPBoard dimensions133,35 x 30 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantYes  | JEDEC Norm                | PC3-10600R             |  |  |
| Type RDIMM (ECC Registered)  Number of pins 240 Pin DIMM  Memory data transfer rate 1333MHz @ CL9  Speciality DDP  Board dimensions 133,35 x 30 (LxB mm)  Operating temperature 0° C - 85° C  Storage temperature -40° C - +95° C  RoHS compliant Yes  | DRAM Organization         | 2Gx4                   |  |  |
| Number of pins240 Pin DIMMMemory data transfer rate1333MHz @ CL9SpecialityDDPBoard dimensions133,35 x 30 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantYes  | Rank                      | 4Rx4 (4DRx4 DDP)       |  |  |
| Memory data transfer rate1333MHz @ CL9SpecialityDDPBoard dimensions133,35 x 30 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantYes  | Туре                      | RDIMM (ECC Registered) |  |  |
| SpecialityDDPBoard dimensions133,35 x 30 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantYes  | Number of pins            | 240 Pin DIMM           |  |  |
| Board dimensions133,35 x 30 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantYes   | Memory data transfer rate | 1333MHz @ CL9          |  |  |
| Operating temperature  0° C - 85° C  Storage temperature  -40° C - +95° C  RoHS compliant  Yes   | Speciality                | DDP                    |  |  |
| Storage temperature -40° C - +95° C  RoHS compliant Yes  | Board dimensions          | 133,35 x 30 (LxB mm)   |  |  |
| RoHS compliant Yes   | Operating temperature     | 0° C - 85° C           |  |  |
|  | Storage temperature       | -40° C - +95° C        |  |  |
| 600 4000 4   | RoHS compliant            | Yes                    |  |  |
| SRU SP260984   | SKU                       | SP260984               |  |  |
| <b>EAN</b> 4063369294318   | EAN                       | 4063369294318          |  |  |

### overRAMing - maximize your RAM



Most systems - including the Supermicro X8DTU-6TF+ - can be upgraded with more memory than originally specified by the device manufacturer.

Therefore, our memory specialists continuously analyze new memory solutions in selected systems. Due to improved manufacturing technologies, new memories with higher performance and capacity will be tested for stability and functionality.

Then the new memory solutions are released for the respective systems. Use the benefits of larger computer memory capacity with the PHSmemory® overRAMing memory solutions.

https://www.phs-memory.it/-BOR

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



#### System Specifications

The memory is 100% compatible with this sytem:

| System manufacturer      | Supermicro  |
|--------------------------|---|
| Device type              | Server-Mainboard  |
| Device family            | Mainboard X   |
| Device series            | X8D Serie   |
| Device name              | X8DTU-6TF+  |
| Maximum memory*          | 384GB ECC / 48GB according to manufacturer  |
| Number of memory sockets | 12  |
| Annotation               | You can use ECC UDIMM or RDIMM, but not mixed in the server. 48GB maximum with UDIMM (12 x 4GB) 384GB maximum with RDIMM (12 x 32GB). Optimal performance: Distribute the memories evenly across the memory slots and CPUs. We are happy to advise you! |

<sup>\*</sup> The specifications for the maximum memory upgrade may differ from those of the manufacturer Supermicro. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

 $Memory\ modules\ with\ our\ over RAMing-symbol\ are\ approved\ by\ us\ for\ maximum\ memory\ expansion.$ 

#### Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
  - Do not touch the gold pins of the memory module
  - Only touch the sides of the memory module
  - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



#### Further memory options for Supermicro X8DTU-6TF+

| Size | SKU      | Technology | Туре                             | Number of pins | Brand       | Reference no. |
|------|----------|------------|----------------------------------|----------------|-------------|---------------|
| 4GB  | SP260983 | DDR3       | UDIMM ECC<br>(ECC<br>unbuffered) | 240 Pin DIMM   | PHS-memory® |               |
| 8GB  | SP580298 | DDR3       | UDIMM ECC<br>(ECC<br>unbuffered) | 240 Pin DIMM   | PHS-memory® |               |
| 8GB  | SP260982 | DDR3       | UDIMM ECC<br>(ECC<br>unbuffered) | 240 Pin DIMM   | PHS-memory® |               |
| 8GB  | SP260978 | DDR3       | RDIMM (ECC<br>Registered)        | 240 Pin DIMM   | PHS-memory® |               |
| 16GB | SP260980 | DDR3       | RDIMM (ECC<br>Registered)        | 240 Pin DIMM   | PHS-memory® |               |
| 8GB  | SP260979 | DDR3       | RDIMM (ECC<br>Registered)        | 240 Pin DIMM   | PHS-memory® |               |
| 32GB | SP260984 | DDR3       | RDIMM (ECC<br>Registered)        | 240 Pin DIMM   | PHS-memory® |               |
| 16GB | SP260981 | DDR3       | RDIMM (ECC<br>Registered)        | 240 Pin DIMM   | PHS-memory® |               |
| 32GB | SP260985 | DDR3       | RDIMM (ECC<br>Registered)        | 240 Pin DIMM   | PHS-memory® |               |

#### PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.





#### Contact Information

PHS-electronic gmbh - www.phs-memory.it - Karl-Götz-Str. 5 97424 Schweinfurt Germania

Phone: +49 9721 784678 E-Mail: info@phs-memory.it Web: www.phs-memory.it

#### Product Datasheet | SP260984 32GB Computer memory for X8DTU-6TF+



All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.it