
## phs memory®

## 16GB Computer memory DDR3 for Supermicro SuperServer 6027TR-H70FRF RDIMM



#### PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



## Memory Specification

CONSIDER TO THE REPORT OF THE	Dmm

Memory technologyDECC supportyet	DDR3		
ECC support ye			
	es		
JEDEC Norm	PC3-12800R		
DRAM Organization 10	Gx4		
Rank 2	Rx4		
Type R	RDIMM (ECC Registered)		
Number of pins 24	40 Pin DIMM		
Memory data transfer rate	600MHz @ CL11		
Speciality -,	, DDP		
Board dimensions 1	33,35 x 30 (LxB mm)		
<b>Operating temperature</b> 0°	)° C - 85° C		
Storage temperature -4	40° C - +95° C		
RoHS compliant ye	es		
SKU SI	P252979		
<b>EAN</b> 40	063369212787		
Board dimensions       1.         Operating temperature       0°         Storage temperature       -4	33,35 x 30 (LxB mm) )° C - 85° C 40° C - +95° C		

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



## System Specifications

The memory is 100% compatible with this sytem:

System manufacturer	Supermicro			
Device type	Server			
Device family	SuperServer			
Device series	6027 Serie			
Device name	SuperServer 6027TR-H70FRF			
Maximum memory*	256GB			
Number of memory sockets	8			
Annotation	ECC DIMM, Registered DIMM and Load Reduced LRDIMM memory modules must not be mixed. Je Prozessor können 4 Computer memory installiert werden.			

\* The specifications for the maximum memory upgrade may differ from those of the manufacturer Supermicro. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

## Information on memory allocation

#### Information on memory configuration

The following technical specifications should be considered in advance:

- The device supports ECC DIMM (with error correction code) or RDIMM (Registered DIMM) RAM memories. RDIMM
  memories are recommended when large memory capacities are to be achieved.
- The different memory technologies (ECC / RDIMM) may not be mixed.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which memory technology (ECC/ RDIMM) is already installed in the system.
- Memory slots without a processor may not be used.
- A higher memory clock of the memory module automatically adapts to the memory clock specified by the system. This can be the case especially with larger capacities.
- When using 4Rank (4Rx..) RDIMM memories, only 2 of 3 memory slots can be used per memory channel.

#### Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
  - Do not touch the gold pins of the memory module
  - Only touch the sides of the memory module



- Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.

# phs memory®

## Further memory options for Supermicro SuperServer 6027TR-H70FRF

Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
8GB	SP252982	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
16GB	SP252979	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
32GB	SP252980	DDR3	RDIMM (ECC Registered)	240 Pin DIMM	PHS-memory®	
32GB	SP252978	DDR3	LRDIMM (ECC LR DIMM)	240 Pin DIMM	PHS-memory®	

#### PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

5 Jahre Garantie

For more information on warranty and service please visit https://www.phs-memory.it/-W5Y

## Contact Information

PHS-electronic gmbh - www.phs-memory.it -Karl-Götz-Str. 5 97424 Schweinfurt Germania Phone: +49 9721 784678 E-Mail: info@phs-memory.it Web: www.phs-memory.it

All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.it