

16GB Computer memory DDR4 for Supermicro SuperServer F618R2-RC0PT+ RDIMM






Your benefits ✓ verified quality memory ✓ 5 years warranty Warranty details see last page ✓ 100% compatible ✓ free support on our hotline ✓ fast delivery

PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



Memory Specification



| Memory size | 16GB |
|---------------------------|-------------------------|
| Memory technology | DDR4 |
| ECC support | yes |
| JEDEC Norm | PC4-2133P-R |
| Туре | RDIMM (ECC Registered) |
| Number of pins | 288 Pin DIMM |
| Memory data transfer rate | 2133MHz @ CL15 |
| Voltage | 1,2 Volt |
| Speciality | - |
| Board dimensions | 133,35 x 31,25 (LxB mm) |
| Operating temperature | 0° C - 85° C |
| Storage temperature | -40° C - +95° C |
| RoHS compliant | yes |
| SKU | SP263623 |
| EAN | 4063369319363 |
| | |

overRAMing - maximize your RAM



Most systems - including the Supermicro SuperServer F618R2-RC0PT+ - can be upgraded with more memory than originally specified by the device manufacturer.

Therefore, our memory specialists continuously analyze new memory solutions in selected systems. Due to improved manufacturing technologies, new memories with higher performance and capacity will be tested for stability and functionality.

Then the new memory solutions are released for the respective systems. Use the benefits of larger computer memory capacity with the PHSmemory® overRAMing memory solutions.

https://www.phs-memory.it/-BOR

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



System Specifications

The memory is 100% compatible with this sytem:

| System manufacturer | Supermicro | | |
|--------------------------|---------------------------------------|--|--|
| Device type | Server | | |
| Device family | SuperServer | | |
| Device series | F618 Serie | | |
| Device name | SuperServer F618R2-RC0PT+ | | |
| Maximum memory* | 4TB / 128GB according to manufacturer | | |
| Number of memory sockets | 16 | | |
| | | | |

^{*} The specifications for the maximum memory upgrade may differ from those of the manufacturer Supermicro. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Memory modules with our overRAMing-symbol are approved by us for maximum memory expansion.

Information on memory allocation

Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- Memory slots without a processor may not be used.
- If memory modules are provided with higher speeds than specified by the system, the memory speed is automatically adjusted to the system specifications.

memory for Intel Xeon CPUs:

| CPU / System | RDIMM | LRDIMM |
|-----------------|-----------------|------------------|
| | | |
| Xeon E5-16xx v3 | 8GB RDIMM | 32GB LRDIMM |
| Xeon E5-26xx v3 | 16GB RDIMM | 64GB LRDIMM DDP |
| Xeon E5-46xx v3 | 32GB RDIMM | 128GB LRDIMM DDP |
| | 64GB RDIMM DDP | 128GB LRDIMM 3DS |
| | 128GB RDIMM 3DS | 256GB LRDIMM 3DS |
| | 256GB RDIMM 3DS | |



Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
 - Do not touch the gold pins of the memory module
 - Only touch the sides of the memory module
 - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



Further memory options for Supermicro SuperServer F618R2-RC0PT+

| 8GB SP263626 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 16GB SP263623 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 32GB SP263624 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP263689 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 64GB SP467333 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP474688 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP467335 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP467329 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP467337 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® | Size | SKU | Technology | Туре | Number of pins | Brand | Reference no. |
|---|-------|----------|------------|------|----------------|-------------|---------------|
| Registered) 32GB SP263624 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP263689 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 64GB SP467333 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP474688 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP467335 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP467329 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP467337 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® | 8GB | SP263626 | DDR4 | • | 288 Pin DIMM | PHS-memory® | |
| Registered) 64GB SP263689 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 64GB SP467333 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP474688 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP467335 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP467329 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP467337 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® | 16GB | SP263623 | DDR4 | • | 288 Pin DIMM | PHS-memory® | |
| LR DIMM) LR DIMM) 64GB SP467333 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP474688 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP467335 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP467329 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP467337 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® | 32GB | SP263624 | DDR4 | • | 288 Pin DIMM | PHS-memory® | |
| Registered) 3DS 128GB SP474688 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP467335 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP467329 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP467337 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® | 64GB | SP263689 | DDR4 | • | 288 Pin DIMM | PHS-memory® | |
| LR DIMM) 128GB SP467335 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP467329 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP467337 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® | 64GB | SP467333 | DDR4 | , | 288 Pin DIMM | PHS-memory® | |
| Registered) 3DS 128GB SP467329 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP467337 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® | 128GB | SP474688 | DDR4 | • | 288 Pin DIMM | PHS-memory® | |
| LR DIMM) 3DS 256GB SP467337 DDR4 RDIMM (ECC 288 Pin DIMM PHS-memory® | 128GB | SP467335 | DDR4 | , | 288 Pin DIMM | PHS-memory® | |
| (| 128GB | SP467329 | DDR4 | • | 288 Pin DIMM | PHS-memory® | |
| | 256GB | SP467337 | DDR4 | , | 288 Pin DIMM | PHS-memory® | |
| 256GB SP467330 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory® LR DIMM) 3DS | 256GB | SP467330 | DDR4 | • | 288 Pin DIMM | PHS-memory® | |

PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.it/-W5Y



Contact Information

PHS-electronic gmbh - www.phs-memory.it - Karl-Götz-Str. 5 97424 Schweinfurt Germania

Phone: +49 9721 784678 E-Mail: info@phs-memory.it Web: www.phs-memory.it

Product Datasheet | SP263623 16GB Computer memory for SuperServer F618R2-RC0PT+



All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.it